Rolltex™ PSS

Resilient Tire

Dependable resilient tires engineered for indoor and outdoor, low-intensity material handling applications. Designed to deliver reliable performance, long service life, and exceptional value.



Why Choose Rolltex™

- ✓ Premium Tread Design
- ✓ Excellent Lateral Stability
- ✓ Long Wear Life
- ✓ Smooth Ride Comfort
- ✓ Resists Chunking & Tearing
- ✓ Exceptional Value

ARMADILLO TIRE

ArmadilloTire.com
209 South Jefferson Avenue

Phone: (855) 860-5618
McGregor, TX. 76657

Rolltex™ PSS

Resilient Tires



Rolltex Pneumatic Shaped Solid Tires are engineered with a premium three-stage construction and a reinforced braided wire bead to help prevent tire slippage on the wheel. Designed to run cooler and last longer, they feature an aggressive tread pattern that delivers dependable traction across a variety of material handling applications—all while providing exceptional value and a low total cost of ownership.

Rolltex PSS Available Tire Sizes

				Tire Dimensions			Load Capacity (lbs)				
							Counter Balanced Lift Trucks Up to 15 mph		Other Vehicles Up to...		
No.	Tire Size	Rim Size	Approx. Tire Qty. Per 20' FCL	Tread Width (in.)	Overall Width (in.)	Overall Diameter (+/- 2%) (in.)	Load Wheels	Steering Wheels	15 mph	6 mph	4 mph
1	4.00-8	3.00D-8	1,600	4	4	16	2,094	1,609	1,609	1,896	2,094
2	15x4 1/2-8	3.00D-8	1,900	4	4	15	2,293	1,764	1,764	2,083	2,293
3	5.00-8	3.00D-8	1,060	4	5	18	3,120	2,403	2,403	2,833	3,120
4	5.00-8	3.25I-8	1,060	4	5	18	3,120	2,403	2,403	2,833	3,120
5	16x6-8	4.33R-8	1,200	5	6	17	3,296	2,535	2,535	2,998	3,296
6	18x7-8	4.33R-8	900	5	6	18	4,729	3,638	3,638	4,288	4,729
7	140/55-9	4.00E-09	1,400	4	5	15	2,579	1,984	1,984	2,337	2,579
8	6.00-9	4.00E-09	700	5	6	21	4,156	3,197	3,197	3,770	4,156
9	21x8-9	6.00E-09	650	6	7	21	6,074	4,674	4,674	5,512	6,074
10	6.50-10	5.00F-10	520	5	6	23	5,159	3,968	3,968	4,685	5,159
11	200/50-10	6.50F-10	900	6	7	18	5,445	4,189	4,189	4,938	5,445
12	23x9-10	6.50F-10	400	6	8	23	7,595	5,842	5,842	6,889	7,595
13	7.00-12	5.00S-12	375	5	7	26	6,437	4,938	4,938	5,831	6,437
14	23x10-12	8.00G-12	300	8	9	23	8,311	6,393	6,393	7,540	8,311
15	27x10-12	8.00G-12	265	8	9	27	8,598	6,614	6,614	7,804	8,598
16	315/45-12	10.00G-12	320	10	11	23	9,888	7,606	7,606	8,973	9,888
17	7.00-15	5.5-15	300	6	7	28	7,815	6,008	6,008	7,088	7,815
18	8.25-15	6.5-15	160	7	8	32	10,472	8,047	8,047	9,480	10,472
19	28x9-15*	7.0-15	285	7	9	27	8,598	6,614	6,614	7,804	8,598
20	250-15	7.0-15	220	7	9	28	10,461	8,047	8,047	9,502	10,461
21	250-15	7.5-15	220	7	9	28	10,461	8,047	8,047	9,502	10,461
22	300-15	8.0-15	150	9	10	32	12,897	9,921	9,921	11,707	12,897
23	28x12.5-15**	9.75-15	130	11	12	27	12,544	9,645	9,645	11,387	12,544
24	355/65-15	9.75-15	130	10	12	32	17,196	13,228	12,015	14,176	15,620
25	10.00-20	7.0-20	80	10	11	40	13,228	11,023	11,023	12,015	13,228
26	10.00-20	7.5-20	80	10	11	40	13,228	11,023	11,023	12,015	13,228
27	10.00-20	8.0-20	80	10	11	40	13,228	11,023	11,023	12,015	13,228
28	12.00-20	8.0-20	70	8	11	43	16,667	13,889	13,889	15,135	16,667
29	12.00-20	8.5-20	70	8	11	43	16,667	13,889	13,889	15,135	16,667

ARMADILLO TIRE
ArmadilloTire.com
209 South Jefferson Avenue
Phone: (855) 860-5618
McGregor, TX. 76657