









TG-AIRIDE



Unique Features:

1. Special designed tread pattern for telehandler and grader applications.
2. Excellent tread compound formula provide the extraordinary chunking and cut resistance properties.
3. Unique two aperture sidewall design ensure best riding comfort.

13.00-24 is replacement for	
370/75-28	315/95-28
330/85-28	13.00-28

14.00-24 is replacement for	
15.5-25	14.00-28
17.5-25	360/85-28
400/75-28	- -

Available Qualities:

PREMIUM COMPOUND
STANDARD COMPOUND
WHITE NON-MARKING
GREY NON-MARKING
ANTI-STATIC COMPOUND
SPECIAL COMPOUNDS ON REQUEST

Tire Size	Standard Rim	Heel Type		Dimensions (")		Load Capacity (lb)			
						Telehandler/Grager			
		Quick	Standard	Section Width	Outer Diameter +/- 2%	3.7 mph	6.2 mph	15.5 mph	Static (0 mph)
13.00-24	8.50V-24	□	◆	12.4	50.8	16865	15355	14054	20426
14.00-24	8.50V-24	□	◆	13.8	52.6	18651	16954	15543	23468

□ Under Development ◆ Available

Armadillo Tire, LLC
209 South Jefferson Avenue
McGregor TX 76657
www.armadillotire.com
Toll Free +1(855)860-5618

CON-Series



EXMILE CURED-ON solid tires provide a high percentage of natural rubber in the tread compound, giving them the longest wear possible even in the most extreme applications and offering low rolling resistance to ensure longer battery life or lower fuel consumption. Exmile's super adhesion strength between the compound and steel will also ensure an extended life. These traits make EXMILE the best cured-on tire manufacturer for either the small or global OEM customers. It is also the best choice for any aftermarket application where the lowest cost of ownership(cost per hour used) is desired.

These tires are approved by the following OEM customers around the globe.

Size & Specifications

MANITOU Genie AIRO Dingli Machinery

SKYJACK

Model No.	OE Tire Size	Exmile Tire Size	Photo
SJ III - 3219	12X4(72) WITH BRAKE	12X4(72) WITH BRAKE	
SJ III - 3219	12X4(72) W/O BRAKE	12X4(72) W/O BRAKE	
SJ III - 3220, 3226, 4626, 4632	16X5(86) WITH BRAKE	16X5(86) WITH BRAKE	
SJ III - 3220, 3226, 4626, 4632	16X5(86) W/O BRAKE	16X5(86) W/O BRAKE	

GENIE

Model No.	OE Tire Size	Exmile Tire Size	Photo
Z-30/20N Z-30/20N RJ	22X7X17.75	22X7X17.75	
GS-1530 GS-1532 GS-1930 GS-1932	12×4.5×8	12×4.5×8	
GS-MODELS: 4047, 2032 2632, 3232 2046, 2646	15×5×11	15×5×11	

JLG

Model No.	OE Tire Size	Exmile Tire Size	Photo
2030ES 2630ES 2646ES 3246ES	406x125	406x125	
2148RS	16x5 LUG	16x5 LUG	
2148RS	16x5 RIB	16x5 RIB	
1930ES	323x100	323x100	

NOTE:

ADDITIONAL SIZES AND STYLES ARE AVAILABLE, CONTACT US TO CONFIRM YOUR SPECIFIC REQUIREMENTS

SKS-Series

SKS-Airide





Special sidewall AIRIDE design makes excellent cushion function and driving comfort.



SKS-DL

Size & Specifications

Tire Size	Standard Rim	Heel Type		Dimensions (inch)		Load Capacity (lb)					
						Forklift		Other Vehicles			
		Quick	Standard	Section Width	Outer Diameter +/- 2%	Load Wheel 15.5 mph	Steer Wheel 15.5 mph	3.7 mph	6.2 mph	15.5 mph	Static (0 mph)
31x10-20△ (10-16.5)	7.50-20	◆	□	9.3	30.9	8,885	6,834	8,885	8,069	6,834	10,318
	7.50V-20	◆	◆								
33x12-20* (12-16.5)	7.50-20	◆	□	11.3	32.7	11,465	8,818	11,464	10,406	8,818	13,316
	7.50V-20	◆	◆								
36x14-20 (14-17.5)	7.50-20	◆	□	12.8	35.8	13,614	10,472	13,614	12,307	10,472	15,818
	7.50V-20	◆	□								

△ SKS Airide & Eco-SKS are both available, shallower tread depath ECO-SKS is also with non-side-hole STABIMATE design. * Extra Deep Lug (SKS-DL)pattern is also available.

□ Under Development ◆ Available

ARMADILLO TIRE, LLC

WWW.ARMADILLOTIRE.COM

209 South Jefferson Avenue

Phone: (855) 860-5618

McGregor, TX 76657